

AIR LIQUIDE

Pressure Regulators, Bottle Pressure Regulators, Relief Valves Stainless Steel SS 316L - Brass

Pressure Regulator



DLM 240-15-50
P/N AL423321
Brass
Single stage
Inlet pressure (max. psig): 3480
Outlet control range (psig): 7 to 218
Flow capacity (l/min): 833 (N₂)
Operating temperature (°F): -5 to 120

DLM 240-50-100
P/N AL423308
Brass
Single stage
Inlet pressure (max. psig): 3480
Outlet control range (psig): 73 to 725
Flow capacity (l/min): 1667 (N₂)
Operating temperature (°F): -5 to 120



DIM 240-3-5
P/N AL422501
SS 316 L
Single stage
Inlet pressure (max. psig): 3480
Outlet control range (psig): 4.4 to 44
Flow capacity (l/min): 83 (N₂)
Operating temperature (°F): -5 to 120

DIM 240-30-30
P/N AL415995
SS 316 L
Single stage
Inlet pressure (max. psig): 3480
Outlet control range (psig): 73 to 435
Flow capacity (l/min): 500 (N₂)
Operating temperature (°F): -5 to 120



BSI 50-1-2
P/N AL423103
SS 316 L
Single stage
Inlet pressure (max. psig): 725
Outlet control range (psig): 0.73 to 15
Flow capacity (l/min): 33 (N₂)
Operating temperature (°F): -5 to 120

Bottle Pressure Regulators



HBD 240-10-12

P/N AL422163

Brass

Dual stage

Inlet pressure (max. psig): 3480

Outlet control range (psig): 1.5 to 100

Flow capacity (l/min): 157 (N₂)

Operating temperature (°F): -40 to 165



HBD 240-10-12-S

P/N AL422164

SS 316 L

Dual stage

Inlet pressure (max. psig): 3480

Outlet control range (psig): 1.5 to 100

Flow capacity (l/min): 157 (N₂)

Operating temperature (°F): -40 to 165

Relief Valves



SV 805 ES - SS 316 L

P/N AL421145

SV 805 MS - brass

P/N AI421144

Connections

Inlet: G3/8

Outlet diameter (mm): 6

Outlet pressure to atmosphere (psig): 232 (others on request)